

E40 F series

108mm~430mm

General Specifications

- Motor : Shaded pole AC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Frequency	Rated Current	Input Power	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B						C	V	Hz	A		
CE40090A11	98	108	134	110	60	0.11	9	3150	1.0	35.33	2.5	88.33	38	520
CE40090A22	98	108	134	220	50	0.07	11	2700	0.8	28.26	1.8	63.60	36	520
CE40150A11	160	170	196	110	60	0.12	10	2800	1.4	49.46	2.7	95.40	38	570
CE40150A22	160	170	196	220	50	0.07	11	2600	1.2	42.40	1.9	67.13	36	570
CE40190A11	198	208	234	110	60	0.12	11	2350	1.4	49.46	2.8	98.93	35	590
CE40190A22	198	208	234	220	50	0.07	12	2550	1.4	49.46	2.0	70.67	36	590
CE40290A11	300	310	356	110	60	0.21	16	2200	2.1	74.20	2.9	102.47	36	720
CE40290A22	300	310	356	220	50	0.09	14	2400	2.4	84.80	2.1	74.20	38	720
CE40350A11	348	370	416	110	60	0.13	13	2000	2.2	77.73	3.0	106.0	41	790
CE40350A22	348	370	416	220	50	0.11	14	2200	2.6	91.87	2.4	84.80	42	790
CE40420A11	420	430	494	110	60	0.11	14	1800	2.4	84.80	3.2	113.07	43	820
CE40420A22	420	430	494	220	50	0.11	15	1800	2.4	84.80	2.6	91.87	44	820

