

E48 Useries

154mm~384mm

General Specifications

- Motor : Shaded pole AC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Frequency	Rated Current	Input Power	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
Part NO.	A	B	C	V	Hz	A	W	RPM	m ³ /min	CFM	mm-Aq	In-H ₂ O	dBA	g
CE48180A11	188	154	247	110	60	0.22	11.5	1300	1.06	37.45	1.4	0.055	40	660
CE48180A22	188	154	247	220	50	0.10	12.5	1300	1.06	37.45	1.4	0.055	40	660
CE48250A11	250	216	319	110	60	0.38	22	1600	2.25	79.50	1.6	0.062	46	720
CE48250A22	250	216	319	220	50	0.22	23	1600	2.25	79.50	1.6	0.062	46	720
CE48300A11	300	266	269	110	60	0.41	24	1300	1.78	62.89	1.8	0.070	41	760
CE48300A22	300	266	269	220	50	0.19	23	1300	1.78	62.89	1.8	0.070	41	760
CE48350A11	348	314	417	110	60	0.40	25	1400	2.63	92.93	2.0	0.078	42	790
CE48350A22	348	314	417	220	50	0.22	26	1400	2.63	92.93	2.0	0.078	42	790
CE48420A11	418	384	487	110	60	0.39	24	1300	2.5	88.33	2.2	0.086	48	820
CE48420A22	418	384	487	220	50	0.19	25	1300	2.5	88.33	2.2	0.086	48	820

