

E50 P series

110mm~432mm

General Specifications

- Motor : Shaded pole AC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Frequency	Rated Current	Input Power	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B						C	V	Hz	A		
CE50090A11	100	110	160	110	60	0.13	9.5	2900	1.0	35.33	1.0	0.039	34	580
CE50090A22	100	110	160	220	50	0.08	12	2660	0.9	31.80	0.8	0.031	33	580
CE50150A11	160	170	225	110	60	0.13	10.5	2100	1.31	46.28	1.2	0.047	36	620
CE50150A22	160	170	225	220	50	0.08	13	2600	1.66	58.65	1.4	0.055	38	620
CE50190A11	200	210	266	110	60	0.19	15	2600	1.6	56.53	1.2	0.047	37	740
CE50190A22	200	210	266	220	50	0.09	13	2500	1.5	53.00	0.9	0.035	36	740
CE50290A11	300	310	375	110	60	0.30	21	2900	2.7	95.40	2.0	0.078	42	1000
CE50290A22	300	310	375	220	50	0.14	18.5	2600	2.6	91.87	1.5	0.059	41	1000
CE50350A11	362	372	437	110	60	0.29	21	2800	2.9	102.47	1.7	0.066	39	1100
CE50350A22	362	372	437	220	50	0.14	19	2550	2.7	95.40	1.6	0.062	38	1100
CE50420A11	422	432	497	110	60	0.28	33	1700	2.25	79.50	1.8	0.070	42	1220
CE50420A22	422	432	497	220	50	0.24	28	2200	3.15	111.30	2.0	0.078	45	1220

