

D30 F series

108mm~310mm

General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Current	Rated Speed	Maximun Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B				C	V	A	RPM		
CD30090A12	98	108	132	12	0.15	3200	0.6	22	1.9	0.074	35	180
CD30090A24	98	108	132	24	0.14	3200	0.6	22	1.9	0.074	35	180
CD30150A12	160	170	194	12	0.16	3100	0.8	28	1.8	0.071	37	210
CD30150A24	160	170	194	24	0.15	3100	0.8	28	1.8	0.071	37	210
CD30190A12	198	208	232	12	0.20	2900	1.0	35	1.8	0.071	38	230
CD30190A24	198	208	232	24	0.16	2900	1.0	35	1.8	0.071	38	230
CD30290A12	300	310	338	12	0.22	2600	1.3	46	1.5	0.059	39	290
CD30290A24	300	310	338	24	0.20	2600	1.3	46	1.5	0.059	39	290

