

D40 F series

108mm~370mm

General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B				C	V	A	RPM		
CD40090A12	98	108	134	12	0.20	3000	0.7	24	2.9	0.114	36	210
CD40090A24	98	108	134	24	0.15	3000	0.7	24	2.9	0.114	36	210
CD40150A12	160	170	196	12	0.25	2600	1.0	35	2.6	0.102	36	250
CD40150A24	160	170	196	24	0.20	2600	1.0	35	2.6	0.102	36	250
CD40190A12	198	208	234	12	0.30	2500	1.4	49	2.5	0.098	37	300
CD40190A24	198	208	234	24	0.15	2500	1.4	49	2.5	0.098	37	300
CD40240A12	245	260	286	12	0.35	2500	2.1	74	2.5	0.098	41	400
CD40240A24	245	260	286	24	0.25	2500	2.1	74	2.5	0.098	41	400
CD40290A12	300	310	356	12	0.55	2700	2.7	95	2.4	0.094	43	540
CD40290A24	300	310	356	24	0.35	2700	2.7	95	2.4	0.094	43	540
CD40350A12	360	370	416	12	0.60	2600	3.0	106	2.1	0.082	44	570
CD40350A24	360	370	416	24	0.40	2600	3.0	106	2.1	0.082	44	570

