

# D50 P series

110mm~432mm

## General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



## Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Current	Rated Speed	Maximun Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B				C	V	A	RPM		
CD50090A12	100	110	133	12	0.22	2800	1.0	36	3.5	0.137	35	315
CD50090A24	100	110	133	24	0.12	2800	1.0	36	3.5	0.137	35	315
CD50150A12	160	170	193	12	0.31	2600	1.7	60	4.3	0.169	39	420
CD50150A24	160	170	193	24	0.19	2600	1.7	60	4.3	0.169	39	420
CD50190A12	200	210	246	12	0.60	2500	2.6	91	4.5	0.177	46	580
CD50190A24	200	210	246	24	0.40	2500	2.6	91	4.5	0.177	46	580
CD50250A12	252	262	298	12	0.62	2400	3.0	105	4.8	0.188	45	640
CD50250A24	252	262	298	24	0.40	2400	3.0	105	4.8	0.188	45	640
CD50290A12	300	310	346	12	0.65	2300	3.6	126	4.2	0.165	43	700
CD50290A24	300	310	346	24	0.40	2300	3.6	126	4.2	0.165	43	700
CD50350A12	360	370	406	12	0.75	2200	3.8	133	3.8	0.149	45	750
CD50350A24	360	370	406	24	0.45	2200	3.8	133	3.8	0.149	45	750
CD50420A12	422	432	468	12	0.75	2000	4.0	140	3.6	0.141	46	800
CD50420A24	422	432	468	24	0.45	2000	4.0	140	3.6	0.141	46	800

