

D60 F series

138mm~444mm

General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B				C	V	A	RPM		
CD60120A12	123	138	183	12	0.60	2500	1.7	60	5.1	0.200	44	620
CD60120A24	123	138	183	24	0.40	2500	1.7	60	5.1	0.200	44	620
CD60180A12	184	199	244	12	0.80	2200	2.5	88	3.8	0.149	46	700
CD60180A24	184	199	244	24	0.45	2200	2.5	88	3.8	0.149	46	700
CD60240A12	245	260	305	12	1.0	2000	3.2	117	3.3	0.129	48	770
CD60240A24	245	260	305	24	0.55	2000	3.2	117	3.3	0.129	48	770
CD60300A12	306	321	366	12	0.50	1600	3.3	113	1.8	0.070	47	840
CD60300A24	306	321	366	24	0.25	1600	3.3	113	1.8	0.070	47	840
CD60360A12	368	383	428	12	0.55	1500	3.7	131	1.7	0.066	48	930
CD60360A24	368	383	428	24	0.25	1500	3.7	131	1.7	0.066	48	930
CD60420A12	429	444	489	12	0.60	1400	4.4	156	1.7	0.066	50	1000
CD60420A24	429	444	489	24	0.30	1400	4.4	156	1.7	0.066	50	1000

