

D60 Useries

130mm~370mm

General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B				C	V	A	RPM		
CD60120A12	120	130	185	12	0.65	2500	2.0	71	6.3	0.248	49	520
CD60120A24	120	130	185	24	0.40	2500	2.0	71	6.3	0.248	49	520
CD60180A12	180	190	245	12	0.95	2200	2.8	99	5.9	0.232	50	610
CD60180A24	180	190	245	24	0.50	2200	2.8	99	5.9	0.232	50	610
CD60240A12	240	250	305	12	0.50	1600	2.9	102	2.8	0.110	42	690
CD60240A24	240	250	305	24	0.25	1600	2.9	102	2.8	0.110	42	690
CD60300A12	300	310	365	12	0.60	1500	3.5	124	2.6	0.102	43	780
CD60300A24	300	310	365	24	0.30	1500	3.5	124	2.6	0.102	43	780
CD60360A12	360	370	425	12	0.65	1400	4.2	149	2.5	0.980	42	860
CD60360A24	360	370	425	24	0.35	1400	4.2	149	2.5	0.980	42	860

